


TITAN 600W

Total PPF: 1,680 $\mu\text{mol/s}$

The TITAN grow light maximizes crop yield and quality in greenhouses and other indoor grow settings. Its compact power supply and linear design reduces shadows on plants in grow spaces with a lot of natural sunlight. These light systems feature a unique copper pipe design for optimal heat dissipation and deliver the highest efficacy and light output, reducing the fixture count. This lowers the system costs per lit square foot while optimizing daylight needed for fruit, vegetables, or cannabis.





SPECIFICATIONS

TYPICAL INPUT POWER	600 W
TYPICAL PHOTON FLUX (PPF)	1,680 $\mu\text{mol/s}$
PPE	2.8 $\mu\text{mol/J}$
IP-RATING	IP65
OPERATING TEMPERATURE	-40 °F to +104 °F
POWER FACTOR	> 90 %
COLOUR RENDERING INDEX	80 Ra
DIMMING	0-10V Dimmable
THE LIGHT WAVELENGTH	400-800 nm
NET WEIGHT	30.9 Lb (14.0 kg)
LIFETIME	50,000 hrs
WARRANTY	5 Years

All specifications are subject to change. All spec values are typical.

TARGETED SPECTRUM



MODEL ORDERING GUIDE



SERIES CODE	WATTAGE	SPECTRUM	INPUT VOLT	CORD LENGTH	PLUG TYPE	MOUNTING
CHFO1= TITAN	600	CF= Full Phase	S= 110V-277V H= 347-480V	10= 10ft	N5P= NEMA 5-15P N6P= NEMA 6-15P L7P= NEMA L7-15P PT= PIGtails	HK= Hanger Kits DM= Detach Mount

- - - - - -

TITAN 600W

Total PPF: 1,680 $\mu\text{mol/s}$

FIXTURE MOUNTING DIMENSIONS



WARNING

1. The installation should be performed by qualified electricians or technicians.
2. Before conducting any installation, maintenance, or removal, the luminaires should be powered off and cooled down.
3. Do not touch the fixture while it is turned on.
4. If there are any issues with the fixture, do not power off and attempt to repair it unless you are a qualified technician, electrician, or customer service member.

PLUG TYPE CHART

N5P	NEMA 5-15P	
N6P	NEMA 6-15P	
L7P	NEMA L7-15P	
PT	PIGTAILS	

WARRANTY

TITAN product is covered by a **5 year** limited warranty. TITAN grow light warrants to the original purchaser that this product is free from defects in materials and workmanship for the period of 5 years from date of purchase. To obtain warranty service please contact your local distributor or sales rep for further instruction.

CALIVE LLC reserves the right to update all product data sheets at any time. Consult CALIVE marketing specialists for publication updates at hello@calivellc.com

Copyright © 2021–2022 CALIVE LLC, All Rights Reserved.

1460 Park Avenue.
Emeryville, CA 94608 USA
www.calivellc.com